

CompactFlash Scan Card 5XRx

With Antimicrobial Protection

Specification Sheet

PHYSICAL

| | |
|---|--|
| CF Card Dimensions | 46 x x 43 x 3.8 mm (1.8 x 1.7 x 0.15 inches) |
| Scanner Head Dimensions <i>without rubber collar</i> | 39 x 51 x 23 mm (1.6 x 2.0 x 0.90 inches) |
| Total Mass | 37 g (1.3 oz) |
| Antimicrobial Rating (JIS Z2801:2000 Test) | 2.49 on Methicillin-resistant Staphylococcus aureus (MRSA) 6.07 when cleaned with Sani-Cloth® Plus disposable cloth wipes |

ENVIRONMENTAL

| | |
|-----------------------|---|
| Operating Temperature | -4 to +140°F (-20 to +60°C) |
| Storage Temperature | -22 to +158°F (-30 to +70°C) |
| Relative Humidity | 5% to 95% non-condensing |
| Shock | 2000 G, 0.7 ms, half sinus, 3 axes |
| Vibration | 8 G r.m.s., from 10 to 500 Hz, 2 hours per axis, 3 axes |
| Ambient Light | 0 to 100,000 lux |

ELECTRICAL

| | |
|-------------------|--|
| Operating Voltage | 3.3V |
| Power Consumption | Standby: 10 mA (33 mW) Idle: 70 mA (231 mW) Scanning: 460 mA (1518 mW) |

SCANNER PERFORMANCE

| | |
|----------------------------|--|
| Scanner Type | Intermec EA15 High Density 2D imager |
| Types of Bar Codes Decoded | Linear (1D) , Stacked linear, 2D/Matrix, Postal |
| Symbologies Decoded | Australia Post, Aztec, BPO4 State Code, British Post, Canada Post, Codabar, Codablock, Code 11, Code 128, Code 39, Code 93, Data Matrix, Dutch Post, EAN/UCC Composite, GS1 DataBar (RSS), GS1-128 (UCC-128/EAN-128), Interleaved 2 of 5, ISBN, Japan Post, Matrix 2 of 5, Maxicode, MSI, PDF 417/Macro PDF 417/Micro PDF 417, Planet, Plessey, Postnet, QR Code, RSS-14. Standard 2 of 5, Telepen, TLCode 39, UPC/EAN, 4 State Code |
| Scan Repetition Rate | 2D mode: 56 images/sec, auto adaptive 1D emulation mode: 200 images/sec, adaptive |
| Optical Resolution | 752 (H) x 480 (V) pixels, 256 gray levels |
| Print Contrast | Down to 25% |
| Scan Angle | Horizontal: 38.9° Vertical: 25.4° |
| Decode Distance* | 3.8 to 27 cm (1.5 to 10.5 inches) typical |

HARDWARE

| | |
|--------------------|--|
| Interface Standard | CompactFlash Type II PC Card (PCMCIA) with Type II adapter (sold separately, SKU# AC4001-515) |
| Compatibility | Windows COM port, CompactFlash Spec. 2.0 |

*Decode distance depends on symbol size, symbology, label media, W-N ratio, scan angle

| | | |
|----------|--------------------------|--|
| SOFTWARE | Operating System Support | Windows Mobile 6 Classic/Professional Windows Mobile 2003/2003SE/5.0 for Pocket PC Windows Vista, XP |
| | Included Software | Installation Utility SocketScan™ keyboard wedge software Socket Floating Trigger |

| | | |
|------------------|----------------|--|
| PACKAGE CONTENTS | Included Items | CompactFlash Scan Card 5XRx Extra rubber collar for non SoMo devices CD with software and user documentation |
|------------------|----------------|--|

| | | |
|-------|--------------------------|--|
| LEGAL | Warranty | Scanner: One year Accessories: 90 days SocketCare™ enhanced service program available separately, www.socketmobile.com/support/socketcare |
| | Certification/Compliance | FCC Part 15, Class B, CE EN55024:2003, C-TICK s.182, IEC60825-1, RoHS, VCCI Class B |

| | | |
|-----|-------------|-------------|
| SKU | Single unit | IS5040-1150 |
| | 20 pack | IS5041-1151 |



Sales Offices

Corporate Headquarters:

39700 Eureka Drive
Newark, CA 94560 USA

Web: socketmobile.com

Phone: +1-510-933-3000

USA & Canada Toll Free: 800-552-3300

Fax: +1-510-933-3030

Online: socketmobile.com/contact

© 2009 Socket Mobile, Inc. Socket, the Socket logo, CompactFlash Scan Card, SocketScan, SoMo, and Business Mobility Now! are registered trademarks or trademarks of Socket Mobile, Inc. All other brand and product names are trademarks of their respective holders. 6450-00193D 12/2009